Top Dog Manufacturing

26 Linkletter Avenue Summerside, PE Canada C1N 4J9
 TEL
 902-887-3063

 TOLL FREE
 1-800-472-2412

 EMAIL
 topdoq@toqdoqmfg.com



Laundering/Cleaning Instructions

Laundering Specifications & Instructions for all Polyurethane Products

IMPORTANT: TOP DOG polyurethane products will NOT absorb fluids or substances at all. The polyurethane has outstanding anti-microbial qualities against bacteria. Bleach will NOT harm the product or discolor it in any way.

CLEANING AND DISINFECTING

- Cleaning and disinfecting is easily done by either using a regular clothes washing machine or through a dip and hang air-dry process.
- Bleach, disinfectant and soaps can be used, depending on protocols.

DIP AND HANG TO AIR-DRY APPLICATION

- Dip, and swish the product around well, in a drum of cleaning/disinfectant fluid, depending upon your protocols.
- Hang products separately on hooks/hangers to air dry.

REGULAR WASHING MACHINE APPLICATION

- Place product in the washing machine in either cold or hot water, depending upon your protocols;
- Add bleach or any other disinfectant and soaps to the desired concentration levels, depending upon your protocols;
- Run the full regular wash cycle;
- The spin cycle will remove most of the surface water on the product.
- Hang products separately on hooks/hangers to air dry; or machine dry.

MACHINE DRYING

As the material absorbs zero moisture, very little drying time is required.

Air Dry Option:

Set dryer on "air fluff" cycle and tumble dry for 10-15 minutes.

Heated Dry

NOTE: If heat is required – <u>maximum temperature</u> cannot exceed 82c.

Set dryer on low or regular heat cycle for 5-10 minutes.

– Note that using a mesh laundry bag can reduce tangling, and product damage.